


# Schedule of Accreditation

issued by

## United Kingdom Accreditation Service

2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

|                                                                                                                                                         |                                                                                                                                                                  |                                                                                                                                                                                         |
|---------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  <p><b>0822</b></p> <p>Accredited to<br/><b>ISO/IEC 17025:2017</b></p> | <h3>Chamois Metrology Limited</h3> <p><b>Issue No: 077    Issue date: 31 October 2019</b></p>                                                                    |                                                                                                                                                                                         |
|                                                                                                                                                         | <p><b>Unit 8 The Centre</b><br/> <b>Holywell Business Park</b><br/> <b>Northfield Road</b><br/> <b>Southam</b><br/> <b>Warwickshire</b><br/> <b>CV47 0FP</b></p> | <p><b>Contact: Mr A Garthwaite</b><br/> <b>Tel: +44 (0)1926 812066</b><br/> <b>Fax: +44 (0)1926 813569</b><br/> <b>E-Mail: lab@chamois.net</b><br/> <b>Website: www.chamois.net</b></p> |
| <p><b>Calibration performed by the Organisations at the locations specified below</b></p>                                                               |                                                                                                                                                                  |                                                                                                                                                                                         |

### Locations covered by the organisation and their relevant activities

#### Laboratory locations:

| Location details                                                                                                                                                                                                                                                                              | Activity                                                                                                                                                                   | Location code |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|
| <p><b>Address</b><br/> Unit 8 The Centre<br/> Holywell Business Park<br/> Northfield Road<br/> Southam<br/> Warwickshire<br/> CV47 0FP</p> <p><b>Local contact</b><br/> Mr A Garthwaite</p>                                                                                                   | <p><u>Mass calibration</u><br/> <u>Electrical calibration</u><br/> <u>Pressure calibration</u><br/> <u>Temperature calibration</u><br/> <u>Dimensional calibration</u></p> | UK            |
| <p><b>Address</b><br/> Metrology division<br/> Unit K2<br/> M7 Business Park<br/> Newhall<br/> Naas<br/> County Kildare<br/> Ireland</p> <p><b>Local contact</b><br/> Mr P Kinsella<br/> <br/> Tel. +353 (0) 45 896660<br/> Fax. +353 (0) 45 896713<br/> Email: info@classictechnology.ie</p> | <p><u>Pressure calibration</u><br/> <u>Electrical calibration</u><br/> <u>Temperature calibration</u><br/> <u>Mass calibration</u><br/> <u>Humidity calibration</u></p>    | IRE           |

#### Site activities performed away from the locations listed above:

| Location details                                                                                                                                                                                                                                                  | Activity                           | Location code |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------|---------------|
| <p>The customer's site or premises must be suitable for the nature of the particular calibrations undertaken and will be the subject of contract review arrangements between the laboratory and the customer</p> <p><b>Local contact</b><br/> Mr A Garthwaite</p> | <p><u>Pressure calibration</u></p> | Site          |



0822

Accredited to  
ISO/IEC 17025:2017

**Schedule of Accreditation**  
issued by  
**United Kingdom Accreditation Service**  
2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

**Chamois Metrology Limited**  
**Issue No: 077 Issue date: 31 October 2019**

Calibration performed by the Organisation at the locations specified

DETAIL OF ACCREDITATION

| Measured Quantity<br>Instrument or Gauge                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Range                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | Calibration and<br>Measurement<br>Capability (CMC)<br>Expressed as an<br>Expanded<br>Uncertainty ( $k = 2$ )                                                                                                                                                                                                                                                                                                                                                                                                                                        | Remarks                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | Location<br>Code     |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|
| <p><b>PRESSURE</b></p> <p>Gas pressure (absolute)</p> <p>Calibration of pressure measuring instruments and gauges</p> <p>Gas pressure (gauge)</p> <p>Calibration of pressure measuring instruments and gauges and "Pressure equivalent" calibration of Dead Weight Testers (pressure balances supplied with an associated mass set) and Effective area calibration of Dead Weight Testers</p> <p>Gas pressure (differential)</p> <p>Calibrations of differential pressure devices with low and high pressure ports at a common mode pressure of 3.5kPa</p> <p>Calibration of pressure indicating instruments and gauges</p> | <p>2 Pa to 160 Pa<br/>160 Pa to 1.4 kPa<br/>1.4 kPa to 15.7 kPa<br/>15.7 kPa to 710 kPa<br/>710 kPa to 27.6 MPa<br/>27.6 MPa to 40 MPa</p> <p>- 100 kPa to - 3.5 kPa<br/>- 3.5 kPa to 0 Pa<br/>0 Pa to 1.4 kPa<br/>1.4 kPa to 15.7 kPa<br/>15.7 kPa to 710 kPa<br/>710 kPa to 27.6 MPa<br/>27.6 MPa to 40 MPa</p> <p>6 Pa to 10 kPa<br/>(Line pressure 3.5 kPa)</p> <p>0 Pa to (7 - line pressure) MPa<br/>(Line pressure 200 kPa to 7 MPa)</p> <p>7 MPa to (27.6 - line pressure) MPa<br/>(Line pressure 7 MPa to 27.6 MPa)</p> <p>0 Pa to (41.4 - line pressure) MPa<br/>(Line pressure 27.6 MPa to 41.4 MPa)</p> | <p>10 %<br/>0.0040 % + 32 Pa<br/>0.0030 % + 1.0 Pa<br/>0.0025 % + 1.0 Pa<br/>0.0025 % + 10 Pa<br/>0.0045 % + 10 Pa</p> <p>0.0035 %<br/>0.0095 % + 0.60 Pa<br/>0.0040 % + 0.50 Pa<br/>0.0022 % + 0.030 Pa<br/>0.0017 %<br/>0.0025 %<br/>0.0045 %</p> <p>0.010 % + 0.060 Pa</p> <p>0.000060 % of line pressure, plus 0.0035 % of differential pressure, plus 5.0 Pa</p> <p>0.000060 % of line pressure, plus 0.0035 % of differential pressure, plus 10 Pa</p> <p>0.000065 % of line pressure, plus 0.0060 % of differential pressure, plus 16 Pa</p> | <p>Calibration of pressure measuring devices with an electrical output may be undertaken.</p> <p>Calibrations may also be performed over an environmental temperature range of -10 °C to +150 °C, with an uncertainty of <math>\pm 1</math> °C on the reported temperature. There will be an additional pressure uncertainty of <math>\pm (30 \text{ ppm} + 0.030 \text{ Pa})</math>.</p> <p>Differential pressure cells may be calibrated using digital communications protocols</p> <p>Calibrations may also be performed over an environmental temperature range of +2 °C to +8 °C with an uncertainty of <math>\pm 1</math> °C on the reported temperature.</p> | <p>UK &amp; Site</p> |



0822  
Accredited to  
ISO/IEC 17025:2017

**Schedule of Accreditation**  
issued by  
**United Kingdom Accreditation Service**  
2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

**Chamois Metrology Limited**  
Issue No: 077 Issue date: 31 October 2019

Calibration performed by the Organisation at the locations specified

| Measured Quantity<br>Instrument or Gauge                                                                                                                                                                                                                                             | Range                                                                                                                                                                                                                                      | Calibration and<br>Measurement<br>Capability (CMC)<br>Expressed as an<br>Expanded<br>Uncertainty ( $k = 2$ )                                                                                                                                       | Remarks                                                                                                                                                                                                                                          | Location<br>Code |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|
| <p>PRESSURE (cont'd)</p> <p>Hydraulic pressure (gauge)</p> <p>Calibration of pressure measuring instruments and gauges. "Pressure equivalent" calibration of Dead Weight Testers (Pressure balance with associated mass set). Effective area calibration of Dead Weight Testers.</p> | <p>137 kPa to 200 kPa<br/>200 kPa to 7 MPa<br/>7 MPa to 172 MPa</p> <p>172 MPa to 345 MPa<br/>345 MPa to 500 MPa</p>                                                                                                                       | <p>0.0070 % + 14 Pa<br/>0.0040 % + 16 Pa<br/>0.0040 % +<br/>0.24 ppm/MPa<br/>0.0080 %<br/>0.015 %</p>                                                                                                                                              |                                                                                                                                                                                                                                                  | UK & Site        |
| <p>Hydraulic pressure (absolute)</p> <p>Calibration of pressure measuring instruments and gauges.</p>                                                                                                                                                                                | <p>200 kPa to 7 MPa<br/>7 MPa to 172 MPa</p> <p>172 MPa to 345 MPa<br/>345 MPa to 500 MPa</p>                                                                                                                                              | <p>0.0040 % + 28 Pa<br/>0.0040 % + 0.24<br/>ppm/MPa + 15 Pa<br/>0.0080 %<br/>0.015 %</p>                                                                                                                                                           |                                                                                                                                                                                                                                                  |                  |
| <p>Hydraulic pressure (differential)</p> <p>Calibration of pressure indicating instruments and gauges</p>                                                                                                                                                                            | <p>0 Pa to (172 - line pressure)<br/>MPa (Line pressure 1.7 MPa to<br/>172 MPa)</p>                                                                                                                                                        | <p>0.000060 % of line<br/>pressure plus<br/>0.0055 % of differential<br/>pressure plus 20 Pa</p>                                                                                                                                                   |                                                                                                                                                                                                                                                  |                  |
| <p>MASS</p>                                                                                                                                                                                                                                                                          | <p>Nominal value (g)</p> <p>26 000<br/>20 000<br/>10 000<br/>5 000<br/>2 000<br/>1 000<br/>500<br/>200<br/>100<br/>50<br/>20<br/>10<br/>5<br/>2<br/>1<br/>0.5<br/>0.2<br/>0.1<br/>0.05<br/>0.02<br/>0.01<br/>0.005<br/>0.002<br/>0.001</p> | <p>(mg)</p> <p>26<br/>20<br/>10<br/>5.0<br/>2.0<br/>1.0<br/>0.50<br/>0.20<br/>0.10<br/>0.060<br/>0.050<br/>0.040<br/>0.032<br/>0.024<br/>0.020<br/>0.016<br/>0.012<br/>0.010<br/>0.0080<br/>0.0060<br/>0.0050<br/>0.0040<br/>0.0040<br/>0.0040</p> | <p>Intermediate values can<br/>be calibrated with an<br/>uncertainty not less than<br/>that interpolated from the<br/>next higher and lower<br/>nominal value in the table.</p> <p>Calibrations can be given<br/>in other units as required.</p> | UK               |



0822  
Accredited to  
ISO/IEC 17025:2017

**Schedule of Accreditation**  
issued by  
**United Kingdom Accreditation Service**  
2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

**Chamois Metrology Limited**  
Issue No: 077 Issue date: 31 October 2019

Calibration performed by the Organisation at the locations specified

| Measured Quantity<br>Instrument or Gauge | Range                                                                                                                                                                                                                                                                                                                            | Calibration and<br>Measurement<br>Capability (CMC)<br>Expressed as an<br>Expanded<br>Uncertainty ( $k = 2$ )                                                                                                                                                                 | Remarks                                                                                | Location<br>Code |
|------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|------------------|
| ELECTRICAL                               |                                                                                                                                                                                                                                                                                                                                  |                                                                                                                                                                                                                                                                              |                                                                                        | UK               |
| DC Voltage                               | 0 mV to 200 mV<br>200 mV to 2 V<br>2 V to 20 V<br>20 V to 200 V<br>200 V to 1050 V                                                                                                                                                                                                                                               | 10 ppm + 0.5 $\mu$ V<br>10 ppm + 1.0 $\mu$ V<br>10 ppm + 10 $\mu$ V<br>10 ppm + 200 $\mu$ V<br>10 ppm + 2.0 mV                                                                                                                                                               | All electrical values can be sourced or measured by comparison unless otherwise stated |                  |
| DC Current                               | 0 $\mu$ A to 200 $\mu$ A<br>200 $\mu$ A to 2 mA<br>2 mA to 20 mA<br>20 mA to 100 mA                                                                                                                                                                                                                                              | 20 ppm + 1.0 nA<br>20 ppm + 10 nA<br>20 ppm + 75 nA<br>40 ppm + 150 nA                                                                                                                                                                                                       | Using nominal 10 $\Omega$ shunt                                                        | UK               |
| DC Current                               | 100 mA to 200 mA<br>200 mA to 2 A<br>2 A to 20 A                                                                                                                                                                                                                                                                                 | 35 ppm + 0.70 $\mu$ A<br>250 ppm + 30 $\mu$ A<br>500 ppm + 1.0 mA                                                                                                                                                                                                            |                                                                                        |                  |
| DC Current                               | 100 mA to 202 mA<br>202 mA to 2.02 A<br>2.02 A to 20 A                                                                                                                                                                                                                                                                           | 62 ppm + 5.5 $\mu$ A<br>90 ppm + 72 $\mu$ A<br>330 ppm + 8.0 mA                                                                                                                                                                                                              | These values can be sourced                                                            |                  |
| DC Current                               | 20 A to 1000 A                                                                                                                                                                                                                                                                                                                   | 0.22 % + 100 mA                                                                                                                                                                                                                                                              | Simulation using multi turn coil                                                       |                  |
| DC Resistance                            | 0 $\Omega$ to 2 $\Omega$<br>2 $\Omega$ to 20 $\Omega$<br>20 $\Omega$ to 200 $\Omega$<br>200 $\Omega$ to 2 k $\Omega$<br>2 k $\Omega$ to 20 k $\Omega$<br>20 k $\Omega$ to 200 k $\Omega$<br>200 k $\Omega$ to 2 M $\Omega$<br>2 M $\Omega$ to 20 M $\Omega$<br>20 M $\Omega$ to 200 M $\Omega$<br>200 M $\Omega$ to 1 G $\Omega$ | 15 ppm + 20 $\mu$ $\Omega$<br>15 ppm + 20 $\mu$ $\Omega$<br>15 ppm + 150 $\mu$ $\Omega$<br>15 ppm + 1.0 m $\Omega$<br>15 ppm + 15 m $\Omega$<br>15 ppm + 100 m $\Omega$<br>15 ppm + 1.5 $\Omega$<br>20 ppm + 20 $\Omega$<br>400 ppm + 500 $\Omega$<br>0.35 % + 12 k $\Omega$ |                                                                                        |                  |
| AC VOLTAGE                               | 1 mV to 200 mV<br>20 Hz to 55 Hz<br>55 Hz to 10 kHz<br>10 kHz to 30 kHz<br>30 kHz to 100 kHz                                                                                                                                                                                                                                     | 150 ppm + 15 $\mu$ V<br>120 ppm + 15 $\mu$ V<br>350 ppm + 16 $\mu$ V<br>600 ppm + 20 $\mu$ V                                                                                                                                                                                 |                                                                                        | UK               |
|                                          | 200 mV to 2 V<br>20 Hz to 55 Hz<br>55 Hz to 10 kHz<br>10 kHz to 30 kHz<br>30 kHz to 100 kHz<br>100 kHz to 500 kHz                                                                                                                                                                                                                | 140 ppm + 40 $\mu$ V<br>120 ppm + 40 $\mu$ V<br>260 ppm + 40 $\mu$ V<br>350 ppm + 100 $\mu$ V<br>0.65 % + 15 mV                                                                                                                                                              |                                                                                        |                  |
|                                          | 2 V to 20 V<br>20 Hz to 55 Hz<br>55 Hz to 10 kHz<br>10 kHz to 30 kHz<br>30 kHz to 100 kHz<br>100 kHz to 500 kHz                                                                                                                                                                                                                  | 150 ppm + 260 $\mu$ V<br>140 ppm + 260 $\mu$ V<br>260 ppm + 330 $\mu$ V<br>550 ppm + 1.2 mV<br>0.65 % + 120 mV                                                                                                                                                               |                                                                                        |                  |



0822  
Accredited to  
ISO/IEC 17025:2017

**Schedule of Accreditation**  
issued by  
**United Kingdom Accreditation Service**  
2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

**Chamois Metrology Limited**  
Issue No: 077 Issue date: 31 October 2019

Calibration performed by the Organisation at the locations specified

| Measured Quantity<br>Instrument or Gauge | Range                                                                     | Calibration and<br>Measurement<br>Capability (CMC)<br>Expressed as an<br>Expanded<br>Uncertainty ( $k = 2$ ) | Remarks                               | Location<br>Code |
|------------------------------------------|---------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------|---------------------------------------|------------------|
| AC VOLTAGE (cont'd)                      | 20 V to 200 V<br>20 Hz to 10 kHz<br>10 kHz to 30 kHz<br>30 kHz to 100 kHz | 140 ppm + 7.0 mV<br>260 ppm + 7.0 mV<br>600 ppm + 15 mV                                                      |                                       |                  |
|                                          | 200 V to 1 kV<br>45 Hz to 10 kHz<br>10 kHz to 30 kHz                      | 200 ppm + 25 mV<br>380 ppm + 30 mV                                                                           |                                       |                  |
| AC CURRENT                               | 20 µA to 200 µA<br>55 Hz to 5 kHz<br>5 kHz to 10 kHz                      | 0.050 % + 50 nA<br>0.060 % + 50 nA                                                                           |                                       |                  |
|                                          | 200 µA to 2 mA<br>55 Hz to 10 kHz                                         | 0.050 % + 500 nA                                                                                             |                                       |                  |
|                                          | 2 mA to 20 mA<br>55 Hz to 10 kHz                                          | 0.050 % + 5.0 µA                                                                                             |                                       |                  |
|                                          | 20 mA to 200 mA<br>55 Hz to 10 kHz                                        | 0.050 % + 50 µA                                                                                              |                                       |                  |
|                                          | 200 mA to 2 A<br>55 Hz to 1 kHz                                           | 0.060 % + 500 µA                                                                                             |                                       |                  |
|                                          | 2 A to 20 A<br>55 Hz to 1 kHz                                             | 0.060 % + 4.0 mA                                                                                             |                                       |                  |
| AC CURRENT<br>Generation only            | 25 µA to 200 µA<br>40 Hz to 45 Hz<br>45 Hz to 1 kHz                       | 0.17 % + 410 nA<br>0.080 % + 390 nA                                                                          |                                       | UK               |
|                                          | 200 µA to 2 mA<br>40 Hz to 45 Hz<br>45 Hz to 1 kHz                        | 0.18 % + 1.0 µA<br>0.075 % + 0.70 µA                                                                         |                                       |                  |
|                                          | 2 mA to 20 mA<br>40 Hz to 45 Hz<br>45 Hz to 1 kHz                         | 0.18 % + 1.1 µA<br>0.073 % + 7.4 µA                                                                          |                                       |                  |
|                                          | 20 mA to 200 mA<br>40 Hz to 45 Hz<br>45 Hz to 1 kHz                       | 0.18 % + 120 µA<br>0.077 % + 86 µA                                                                           |                                       |                  |
|                                          | 200 mA to 2 A<br>40 Hz to 45 Hz<br>45 Hz to 1 kHz                         | 0.18 % + 1.1 mA<br>0.085 % + 770 µA                                                                          |                                       |                  |
|                                          | 2 A to 20 A<br>40 Hz to 45 Hz<br>45 Hz to 100 Hz                          | 0.16 % + 11 mA<br>0.037 % + 6.6 mA                                                                           |                                       |                  |
|                                          | 20 A to 100 A at 50 Hz                                                    | 0.22 % + 100 mA                                                                                              | Simulation using a multi<br>turn coil |                  |
|                                          | 100 A to 1000 A at 50 Hz                                                  | 0.22 % + 400 mA                                                                                              |                                       |                  |



0822  
Accredited to  
ISO/IEC 17025:2017

**Schedule of Accreditation**  
issued by  
**United Kingdom Accreditation Service**  
2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

**Chamois Metrology Limited**  
Issue No: 077 Issue date: 31 October 2019

Calibration performed by the Organisation at the locations specified

| Measured Quantity<br>Instrument or Gauge | Range                                                                                                                                                                                 | Calibration and<br>Measurement<br>Capability (CMC)<br>Expressed as an<br>Expanded<br>Uncertainty ( $k = 2$ ) | Remarks                                                                                                                                                                                                                | Location<br>Code |
|------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|
| AC RESISTANCE<br><br>55 Hz to 1 kHz      | 30 $\mu\Omega$ to 10 m $\Omega$<br>10 m $\Omega$ to 100 m $\Omega$<br>100 m $\Omega$ to 1 $\Omega$<br>1 $\Omega$ to 10<br>10 $\Omega$ to 100 $\Omega$<br>100 $\Omega$ to 1 k $\Omega$ | 26 $\mu\Omega$<br>0.26 %<br>0.26 %<br>0.16 %<br>0.16 %<br>0.16 %                                             |                                                                                                                                                                                                                        | UK               |
| CAPACITANCE                              | 1 nF<br>10 nF<br>20 nF<br>50 nF<br>100 nF<br>1 $\mu\text{F}$<br>10 $\mu\text{F}$                                                                                                      | 29 pF<br>61 pF<br>99 pF<br>220 pF<br>370 pF<br>5.1 nF<br>78 nF                                               | For the calibration of<br>measuring devices                                                                                                                                                                            |                  |
| FREQUENCY                                | 10 MHz Clock frequency<br>10 mHz to 80 MHz<br><br>1 mHz to 80 MHz                                                                                                                     | 1.0 parts in $10^8$<br>5.0 parts in $10^8$<br><br>5.0 parts in $10^8 + 5.0$<br>$\mu\text{Hz}$                | Frequency may also be<br>expressed in terms of<br>time; $1/f$ , for repetitive<br>signals or in other units<br>such as revolutions per<br>minute.<br><br>Calibration of measuring<br>devices<br>Calibration of sources | UK               |
| TIME INTERVAL                            | 0 s to 1 day                                                                                                                                                                          | 100 ms                                                                                                       | Manually triggered single<br>events.                                                                                                                                                                                   | UK               |
| RPM                                      | 60 RPM to 60000 RPM                                                                                                                                                                   | 50 ppm + 0.01 RPM                                                                                            | Generate                                                                                                                                                                                                               | UK               |



0822  
Accredited to  
ISO/IEC 17025:2017

**Schedule of Accreditation**  
issued by  
**United Kingdom Accreditation Service**  
2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

**Chamois Metrology Limited**  
Issue No: 077 Issue date: 31 October 2019

Calibration performed by the Organisation at the locations specified

| Measured Quantity<br>Instrument or Gauge              | Range                                                      | Calibration and<br>Measurement<br>Capability (CMC)<br>Expressed as an<br>Expanded<br>Uncertainty ( $k = 2$ ) | Remarks                                                                                                               | Location<br>Code |
|-------------------------------------------------------|------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------|------------------|
| OSCILLOSCOPES                                         |                                                            |                                                                                                              |                                                                                                                       |                  |
| Vertical deflection coefficients                      |                                                            |                                                                                                              |                                                                                                                       | UK               |
| DC                                                    | 30 mV to 300 mV<br>300 mV to 120 V                         | 1.1 %<br>0.30 %                                                                                              | Square-wave & DC<br>signals appropriate for the<br>calibration of oscilloscope<br>vertical deflection<br>coefficients |                  |
| Peak to Peak Voltage 1 kHz                            | 30 mV to 300 mV<br>300 mV to 6 V                           | 1.3 %<br>0.70 %                                                                                              |                                                                                                                       |                  |
| Horizontal deflection<br>coefficients                 |                                                            |                                                                                                              |                                                                                                                       |                  |
| Time                                                  | 10 ns to 1 s                                               | 0.10 %                                                                                                       | Pulse markers                                                                                                         |                  |
|                                                       |                                                            |                                                                                                              | The uncertainties quoted<br>above are based on the<br>readout resolution of<br>typical oscilloscopes.                 |                  |
| ELECTRICAL SIMULATION<br>OF TEMPERATURE               |                                                            |                                                                                                              |                                                                                                                       | UK               |
| Base Metal Thermocouples<br>Noble Metal Thermocouples | -200 °C to +1400 °C<br>0 °C to 500 °C<br>500 °C to 1800 °C | 0.050 °C<br>0.080 °C<br>0.050 °C                                                                             | Excluding automatic CJC                                                                                               |                  |
| Type B (Noble)                                        | 0 °C to 500 °C<br>500 °C to 1800 °C                        | 0.50 °C<br>0.10 °C                                                                                           |                                                                                                                       |                  |
| Type C                                                | 0 °C to 2315 °C                                            | 0.050 °C                                                                                                     |                                                                                                                       |                  |
| Base Metal Thermocouples<br>Noble Metal Thermocouples | -200 °C to +1400 °C<br>0 °C to 500 °C<br>500 °C to 1800 °C | 0.17 °C<br>0.26 °C<br>0.25 °C                                                                                | Including automatic CJC                                                                                               |                  |
| Type B (Noble)                                        | 0 °C to 500 °C<br>500 °C to 1800 °C                        | 0.50 °C<br>0.28 °C                                                                                           |                                                                                                                       |                  |
| Cold Junction Compensation                            | 0 °C to 30 °C                                              | 0.15 °C                                                                                                      |                                                                                                                       |                  |
| Pt 100 resistance<br>thermometer simulation           | -200 °C to +266 °C<br>266 °C to 830 °C                     | 0.011 °C<br>0.015 °C                                                                                         |                                                                                                                       |                  |
| Pt 1000 resistance<br>thermometer simulation          | -200 °C to +266 °C<br>266 °C to 830 °C                     | 0.070 °C<br>0.13 °C                                                                                          |                                                                                                                       |                  |



0822  
Accredited to  
ISO/IEC 17025:2017

**Schedule of Accreditation**  
issued by  
**United Kingdom Accreditation Service**  
2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

**Chamois Metrology Limited**  
Issue No: 077 Issue date: 31 October 2019

Calibration performed by the Organisation at the locations specified

| Measured Quantity<br>Instrument or Gauge                         | Range                                                                                        | Calibration and<br>Measurement<br>Capability (CMC)<br>Expressed as an<br>Expanded<br>Uncertainty ( $k = 2$ ) | Remarks                                                                                                                                                                                                              | Location<br>Code |
|------------------------------------------------------------------|----------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|
| <b>TEMPERATURE</b>                                               |                                                                                              |                                                                                                              |                                                                                                                                                                                                                      |                  |
| Temperature indicators and recorders, with temperature sensor(s) | 0.01 °C (Water Triple Point)<br>-95 °C to 140 °C<br>140 °C to 150 °C<br>150 °C to 650 °C     | 0.0050 °C<br>0.055 °C<br>0.080<br>0.10 °C                                                                    |                                                                                                                                                                                                                      | UK               |
| Resistance thermometers                                          | 0.01 °C (Water Triple Point)<br>-95 °C to 140 °C<br>140 °C to 150 °C<br>150 °C to 650 °C     | 0.0050 °C<br>0.055 °C<br>0.080 °C<br>0.10 °C                                                                 |                                                                                                                                                                                                                      |                  |
| Thermocouples<br>Base Metal                                      | -95 °C to 0 °C<br>0 °C to 30 °C<br>30 °C to 650 °C                                           | 0.40 °C<br>0.10 °C<br>0.40 °C                                                                                |                                                                                                                                                                                                                      |                  |
| Noble Metal<br>Type R and S<br>Type B                            | 0 °C to 650 °C<br>0 °C to 650 °C                                                             | 0.40 °C<br>0.70 °C                                                                                           |                                                                                                                                                                                                                      |                  |
| Metal Block Calibrators and portable liquid baths                | -100 °C to 250 °C<br>250 °C to 650 °C                                                        | 0.050 °C<br>0.13 °C                                                                                          |                                                                                                                                                                                                                      |                  |
| <b>LENGTH</b>                                                    |                                                                                              |                                                                                                              | <b>NOTES</b>                                                                                                                                                                                                         | UK               |
| Orifice plates                                                   | BS EN ISO 5167-2:2003 Bore diameter<br>10 to 700                                             | 8                                                                                                            | RANGE IN MILLIMETRES AND UNCERTAINTY IN MICROMETRES UNLESS OTHERWISE STATED                                                                                                                                          |                  |
| Micrometers, External                                            | BS 870:2008<br>0 to 125                                                                      | Heads:2.0 between any two points                                                                             | The uncertainty quoted is for the departure from either flatness, straightness, parallelism, or squareness, i.e. the distance separating the two parallel planes which just enclose the surface under consideration. |                  |
| Caliper gauges (inc. Vernier, dial and digital)                  | BS 887:2008<br>0 to 150                                                                      | Overall performance 20                                                                                       |                                                                                                                                                                                                                      |                  |
| Dial gauges and dial test indicators                             | BS 907:2008 and BS 2795:1981<br>0 to 100                                                     | 1.0                                                                                                          |                                                                                                                                                                                                                      |                  |
| Length gauges, flat and spherical ended                          | 0 to 100                                                                                     | 1.0 + (8.0 x length in m)                                                                                    |                                                                                                                                                                                                                      |                  |
| <b>ANGLE</b>                                                     |                                                                                              |                                                                                                              |                                                                                                                                                                                                                      |                  |
| Squares, blade type                                              | BS 939:2007<br>50 to 300                                                                     | 3.0<br>(see note 1)                                                                                          |                                                                                                                                                                                                                      |                  |
| Spirit levels                                                    | As BS 3509:1962 and BS 958:1968<br>5 seconds of arc to 60 minutes of arc nominal sensitivity | Mean sensitivity 10 % of nominal<br>Minimum 0.50 seconds of arc                                              |                                                                                                                                                                                                                      |                  |





0822

Accredited to  
ISO/IEC 17025:2017

## Schedule of Accreditation

issued by

**United Kingdom Accreditation Service**

2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

**Chamois Metrology Limited**

Issue No: 077 Issue date: 31 October 2019

Calibration performed by the Organisation at the locations specified

| Measured Quantity<br>Instrument or Gauge                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Range                                                                                                                                                                                                                                                       | Calibration and<br>Measurement<br>Capability (CMC)<br>Expressed as an<br>Expanded<br>Uncertainty ( $k = 2$ )                                                                           | Remarks                                                                                                   | Location<br>Code      |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------|-----------------------|
| FORM<br><br>Straightedges<br>Cast iron, Steel and Granite                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | BS 5204:Part 1:1975<br>BS 5204:Part 2:1977<br>0 to 1800                                                                                                                                                                                                     | 1.0 + (2.0 x length in<br>m)<br>(see Notes)                                                                                                                                            |                                                                                                           | UK                    |
| <p>PRESSURE</p> <p>Gas pressure (absolute)</p> <p>Calibration of pressure<br/>measuring instruments and<br/>gauges</p> <p>Gas pressure (gauge)</p> <p>Calibration of pressure<br/>measuring instruments and<br/>gauges</p> <p>Gas pressure (differential)</p> <p>Calibrations of differential<br/>pressure devices with low<br/>and high pressure ports at a<br/>common mode pressure of<br/>3.5 kPa</p> <p>Hydraulic pressure (gauge)</p> <p>Calibration of pressure<br/>measuring instruments and<br/>gauges</p> <p>Hydraulic pressure (absolute)</p> <p>Calibration of pressure<br/>measuring instruments and<br/>gauges</p> | <p>1.4 kPa to 710 kPa<br/>710 kPa to 10.1 MPa</p> <p>-100 kPa to -1.4 kPa<br/>1.4 kPa to 10 MPa</p> <p>6 Pa to 10 kPa<br/>(Line pressure 3.5 kPa)</p> <p>358 kPa to 3.5 MPa<br/>3.5 MPa to 111.5 MPa</p> <p>458 kPa to 3.6 MPa<br/>3.6 MPa to 111.6 MPa</p> | <p>0.0050 % + 2.0 Pa<br/>0.0050 % + 20 Pa</p> <p>0.0050 %<br/>0.0050 %</p> <p>0.010 % + 0.060 Pa</p> <p>0.0090 % + 30 Pa<br/>0.0075 %</p> <p>0.0090 % + 50 Pa<br/>0.0075 % + 20 Pa</p> | <p>Calibration of pressure<br/>measuring devices with an<br/>electrical output may be<br/>undertaken.</p> | <p>IRE</p> <p>IRE</p> |



0822  
Accredited to  
ISO/IEC 17025:2017

**Schedule of Accreditation**  
issued by  
**United Kingdom Accreditation Service**  
2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

**Chamois Metrology Limited**  
Issue No: 077 Issue date: 31 October 2019

Calibration performed by the Organisation at the locations specified

| Measured Quantity<br>Instrument or Gauge | Range                    | Calibration and<br>Measurement<br>Capability (CMC)<br>Expressed as an<br>Expanded<br>Uncertainty ( $k = 2$ ) | Remarks                                                                                                                                                                                                           | Location<br>Code |
|------------------------------------------|--------------------------|--------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|
| MASS                                     | Nominal value (g)        | (mg)                                                                                                         |                                                                                                                                                                                                                   | IRE              |
|                                          | 20 000                   | 10                                                                                                           | Intermediate values can be calibrated with an uncertainty not less than that interpolated from the next higher and lower nominal value in the table.<br><br>Calibrations can be given in other units as required. |                  |
|                                          | 10 000                   | 5.3                                                                                                          |                                                                                                                                                                                                                   |                  |
|                                          | 5 000                    | 2.7                                                                                                          |                                                                                                                                                                                                                   |                  |
|                                          | 2 000                    | 1.0                                                                                                          |                                                                                                                                                                                                                   |                  |
|                                          | 1 000                    | 0.53                                                                                                         |                                                                                                                                                                                                                   |                  |
|                                          | 500                      | 0.27                                                                                                         |                                                                                                                                                                                                                   |                  |
|                                          | 200                      | 0.10                                                                                                         |                                                                                                                                                                                                                   |                  |
|                                          | 100                      | 0.053                                                                                                        |                                                                                                                                                                                                                   |                  |
|                                          | 50                       | 0.033                                                                                                        |                                                                                                                                                                                                                   |                  |
|                                          | 20                       | 0.027                                                                                                        |                                                                                                                                                                                                                   |                  |
|                                          | 10                       | 0.020                                                                                                        |                                                                                                                                                                                                                   |                  |
|                                          | 5                        | 0.017                                                                                                        |                                                                                                                                                                                                                   |                  |
|                                          | 2                        | 0.013                                                                                                        |                                                                                                                                                                                                                   |                  |
|                                          | 1                        | 0.010                                                                                                        |                                                                                                                                                                                                                   |                  |
|                                          | 0.5                      | 0.0083                                                                                                       |                                                                                                                                                                                                                   |                  |
|                                          | 0.2                      | 0.0067                                                                                                       |                                                                                                                                                                                                                   |                  |
|                                          | 0.1                      | 0.0053                                                                                                       |                                                                                                                                                                                                                   |                  |
|                                          | 0.05                     | 0.0040                                                                                                       |                                                                                                                                                                                                                   |                  |
|                                          | 0.02                     | 0.0033                                                                                                       |                                                                                                                                                                                                                   |                  |
| 0.01                                     | 0.0027                   |                                                                                                              |                                                                                                                                                                                                                   |                  |
| 0.005                                    | 0.0020                   |                                                                                                              |                                                                                                                                                                                                                   |                  |
| 0.002                                    | 0.0020                   |                                                                                                              |                                                                                                                                                                                                                   |                  |
| 0.001                                    | 0.0020                   |                                                                                                              |                                                                                                                                                                                                                   |                  |
| ELECTRICAL<br>DC VOLTAGE                 | 0 mV to 200 mV           | 10 ppm + 1.5 $\mu$ V                                                                                         |                                                                                                                                                                                                                   | IRE              |
|                                          | 200 mV to 2 V            | 10 ppm + 1.5 $\mu$ V                                                                                         |                                                                                                                                                                                                                   |                  |
|                                          | 2 V to 20 V              | 10 ppm + 10 $\mu$ V                                                                                          |                                                                                                                                                                                                                   |                  |
|                                          | 20 V to 200 V            | 10 ppm + 200 $\mu$ V                                                                                         |                                                                                                                                                                                                                   |                  |
|                                          | 200 V to 1 kV            | 10 ppm + 2.0 mV                                                                                              |                                                                                                                                                                                                                   |                  |
| DC CURRENT                               | 0 $\mu$ A to 200 $\mu$ A | 20 ppm + 1 nA                                                                                                | Using nominal 10 $\Omega$ shunt                                                                                                                                                                                   | IRE              |
|                                          | 200 $\mu$ A to 2 mA      | 20 ppm + 10 nA                                                                                               |                                                                                                                                                                                                                   |                  |
|                                          | 2 mA to 20 mA            | 20 ppm + 75 nA                                                                                               |                                                                                                                                                                                                                   |                  |
|                                          | 20 mA to 40 mA           | 50 ppm + 150 nA                                                                                              |                                                                                                                                                                                                                   |                  |
|                                          | 40 mA to 200 mA          | 35 ppm + 700 nA                                                                                              |                                                                                                                                                                                                                   |                  |
|                                          | 200 mA to 2 A            | 250 ppm + 30 $\mu$ A                                                                                         |                                                                                                                                                                                                                   |                  |
|                                          | 2 A to 20 A              | 500 ppm + 1.0 mA                                                                                             |                                                                                                                                                                                                                   |                  |
| 100 mA to 202 mA                         | 130 ppm + 6.6 $\mu$ A    | Calibration of measuring devices by comparison                                                               |                                                                                                                                                                                                                   |                  |
| 202 mA to 2.02 A                         | 150 ppm + 180 $\mu$ A    |                                                                                                              |                                                                                                                                                                                                                   |                  |
| 2.02 A to 20 A                           | 420 ppm + 1.5 mA         |                                                                                                              |                                                                                                                                                                                                                   |                  |
| 20 A to 1500 A                           | 0.22 % + 100 mA          | Simulation using a multi turn coil                                                                           |                                                                                                                                                                                                                   |                  |



0822  
Accredited to  
ISO/IEC 17025:2017

**Schedule of Accreditation**  
issued by  
**United Kingdom Accreditation Service**  
2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

**Chamois Metrology Limited**  
Issue No: 077 Issue date: 31 October 2019

Calibration performed by the Organisation at the locations specified

| Measured Quantity<br>Instrument or Gauge | Range                                                                                                                                                                                                                                                                                                                            | Calibration and<br>Measurement<br>Capability (CMC)<br>Expressed as an<br>Expanded<br>Uncertainty ( $k = 2$ )                                                                                                                                                                       | Remarks                                                                                                       | Location<br>Code |
|------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------|------------------|
| DC RESISTANCE                            | 0 $\Omega$ to 2 $\Omega$<br>2 $\Omega$ to 20 $\Omega$<br>20 $\Omega$ to 200 $\Omega$<br>200 $\Omega$ to 2 k $\Omega$<br>2 k $\Omega$ to 20 k $\Omega$<br>20 k $\Omega$ to 200 k $\Omega$<br>200 k $\Omega$ to 2 M $\Omega$<br>2 M $\Omega$ to 20 M $\Omega$<br>20 M $\Omega$ to 200 M $\Omega$<br>200 M $\Omega$ to 1 G $\Omega$ | 15 ppm + 20 $\mu\Omega$<br>15 ppm + 20 $\mu\Omega$<br>15 ppm + 150 $\mu\Omega$<br>15 ppm + 1.0 m $\Omega$<br>15 ppm + 15 m $\Omega$<br>15 ppm + 100 m $\Omega$<br>15 ppm + 1.5 $\Omega$<br>20 ppm + 20 $\Omega$<br>400 ppm + 500 $\Omega$<br>0.35 % + 12 k $\Omega$                |                                                                                                               | IRE              |
| AC VOLTAGE                               | 1 mV to 200 mV<br>20 Hz to 55 Hz<br>55 Hz to 10 kHz<br>10 kHz to 30 kHz<br><br>30 kHz to 100 kHz<br><br>200 mV to 2 V<br>20 Hz to 55 Hz<br>55 Hz to 10 kHz<br>10 kHz to 30 kHz<br>30 kHz to 100 kHz<br>100 kHz to 500 kHz                                                                                                        | 150 ppm + 15 $\mu\text{V}$<br>120 ppm + 15 $\mu\text{V}$<br>350 ppm + 16 $\mu\text{V}$<br><br>600 ppm + 20 $\mu\text{V}$<br><br>140 ppm + 40 $\mu\text{V}$<br>120 ppm + 40 $\mu\text{V}$<br>260 ppm + 40 $\mu\text{V}$<br>350 ppm + 100 $\mu\text{V}$<br>0.65 % + 15 $\mu\text{V}$ | AC Values can be sourced or measured by comparison up to 1 kHz, above that frequency is for measurement only. | IRE              |
| AC VOLTAGE                               | 2 V to 20 V<br>20 Hz to 55 Hz<br>55 Hz to 10 kHz<br>10 kHz to 30 kHz<br>30 kHz to 100 kHz<br>100 kHz to 500 kHz<br><br>20 V to 200 V<br>20 Hz to 10 kHz<br>10 kHz to 30 kHz<br>30 kHz to 100 kHz<br><br>200 V to 1 kV<br>50 Hz to 10 kHz<br>10 kHz to 30 kHz                                                                     | 150 ppm + 260 $\mu\text{V}$<br>140 ppm + 260 $\mu\text{V}$<br>260 ppm + 330 $\mu\text{V}$<br>550 ppm + 1.2 mV<br>0.75 % + 120 mV<br><br>140 ppm + 7 mV<br>260 ppm + 7 mV<br>600 ppm + 15 mV<br><br>200 ppm + 25 mV<br>380 ppm + 30 mV                                              |                                                                                                               | IRE              |
| AC CURRENT                               | 10 $\mu\text{A}$ to 200 $\mu\text{A}$<br>55 Hz to 5 kHz<br>5 kHz to 10 kHz<br><br>200 $\mu\text{A}$ to 2 mA<br>55 Hz to 10 kHz<br><br>2 mA to 20 mA<br>55 Hz to 10 kHz<br><br>20 mA to 200 mA<br>55 Hz to 10 kHz                                                                                                                 | 0.050 % + 50 nA<br>0.060 % + 50 nA<br><br>0.050 % + 500 nA<br><br>0.050 % + 5.0 $\mu\text{A}$<br><br>0.050 % + 50 $\mu\text{A}$                                                                                                                                                    |                                                                                                               | IRE              |



0822  
Accredited to  
ISO/IEC 17025:2017

**Schedule of Accreditation**  
issued by  
**United Kingdom Accreditation Service**  
2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

**Chamois Metrology Limited**  
Issue No: 077 Issue date: 31 October 2019

Calibration performed by the Organisation at the locations specified

| Measured Quantity<br>Instrument or Gauge | Range                                                          | Calibration and<br>Measurement<br>Capability (CMC)<br>Expressed as an<br>Expanded<br>Uncertainty ( $k = 2$ ) | Remarks                                                                                                                                           | Location<br>Code |
|------------------------------------------|----------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|------------------|
| AC CURRENT (cont'd)                      | 200 mA to 2 A<br>55 Hz to 10 kHz                               | 0.085 % + 500 $\mu$ A                                                                                        | Calibration of measuring<br>devices by comparison                                                                                                 | IRE              |
|                                          | 2 A to 20 A<br>55 Hz to 5 kHz                                  | 0.20 % + 5.0 mA                                                                                              |                                                                                                                                                   |                  |
|                                          | 25 $\mu$ A to 202 $\mu$ A<br>40 Hz to 45 Hz<br>45 Hz to 999 Hz | 0.28 % + 420 nA<br>0.099 % + 390 nA                                                                          |                                                                                                                                                   |                  |
|                                          | 202 $\mu$ A to 2.02 mA<br>40 Hz to 45 Hz<br>45 Hz to 999 Hz    | 0.22 % + 1.2 $\mu$ A<br>0.094 % + 0.80 $\mu$ A                                                               |                                                                                                                                                   |                  |
|                                          | 2.02 mA to 20.2 mA<br>40 Hz to 45 Hz<br>45 Hz to 999 Hz        | 0.23 % + 12 $\mu$ A<br>0.094 % + 7.9 $\mu$ A                                                                 |                                                                                                                                                   |                  |
|                                          | 20.2 mA to 202 mA<br>40 Hz to 45 Hz<br>45 Hz to 999 Hz         | 0.22 % + 120 $\mu$ A<br>0.94 % + 90 $\mu$ A                                                                  |                                                                                                                                                   |                  |
|                                          | 202 mA to 2.02 A<br>40 Hz to 45 Hz<br>45 Hz to 999 Hz          | 0.25 % + 1.2 mA<br>0.11 % + 0.11 mA                                                                          |                                                                                                                                                   |                  |
|                                          | 2.02 A to 20 A<br>40 Hz to 45 Hz<br>45 Hz to 999 Hz            | 0.34 % + 13 mA<br>0.073 % + 4.4 mA                                                                           |                                                                                                                                                   |                  |
|                                          | 20 A to 100 A, 40 Hz to 60 Hz                                  | 0.25 % + 100 mA                                                                                              | Simulation using a multi<br>turn coil                                                                                                             | IRE              |
|                                          | 100 A to 1500 A, 40 Hz to 60 Hz                                | 0.25 % + 400 mA                                                                                              |                                                                                                                                                   |                  |
| CAPACITANCE                              | 1 nF                                                           | 29 pF                                                                                                        | Calibration of measuring<br>devices by comparison                                                                                                 | IRE              |
|                                          | 10 nF                                                          | 58 pF                                                                                                        |                                                                                                                                                   |                  |
|                                          | 20 nF                                                          | 92 pF                                                                                                        |                                                                                                                                                   |                  |
|                                          | 50 nF                                                          | 190 pF                                                                                                       |                                                                                                                                                   |                  |
|                                          | 100 nF                                                         | 360 pF                                                                                                       |                                                                                                                                                   |                  |
|                                          | 1 $\mu$ F                                                      | 5.1 nF                                                                                                       |                                                                                                                                                   |                  |
|                                          | 10 $\mu$ F                                                     | 74 nF                                                                                                        |                                                                                                                                                   |                  |
|                                          | 100 $\mu$ F                                                    | 840 nF                                                                                                       |                                                                                                                                                   |                  |
|                                          | 1 mF                                                           | 13 $\mu$ F                                                                                                   |                                                                                                                                                   |                  |
|                                          | 10 mF                                                          | 130 $\mu$ F                                                                                                  |                                                                                                                                                   |                  |
| FREQUENCY                                | 0.01 Hz to 50 MHz                                              | 5.0 in $10^8$                                                                                                | Frequency may also be<br>expressed in terms of<br>time; $1/f$ , for repetitive<br>signals or in other units<br>such as revolutions per<br>minute. | IRE              |



0822  
Accredited to  
ISO/IEC 17025:2017

**Schedule of Accreditation**  
issued by  
**United Kingdom Accreditation Service**  
2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

**Chamois Metrology Limited**  
Issue No: 077 Issue date: 31 October 2019

Calibration performed by the Organisation at the locations specified

| Measured Quantity<br>Instrument or Gauge  | Range                                                                                                                                                                                                            | Calibration and<br>Measurement<br>Capability (CMC)<br>Expressed as an<br>Expanded<br>Uncertainty ( $k = 2$ ) | Remarks                                                                     | Location<br>Code |
|-------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------|------------------|
| RPM<br>(Revolutions per minute)           | 2 rpm to 10 rpm<br>10 rpm to 100 rpm<br>100 rpm to 1000 rpm<br>1 000 rpm to 10 000 rpm<br>10 000 rpm to 100 000 rpm                                                                                              | 10 ppm + 0.00050 rpm<br>10 ppm + 0.0020 rpm<br>10 ppm + 0.020 rpm<br>10 ppm + 0.20 rpm<br>10 ppm + 2.0 ppm   |                                                                             | IRE              |
| TIME INTERVAL                             | Longer than 100 ms<br>Longer than 80 ns                                                                                                                                                                          | 2.0 ppm + 20 ms<br>2.0 ppm + 80 ns                                                                           | Manually triggered single events.<br>Electronically triggered single events | IRE<br>IRE       |
| RCD                                       |                                                                                                                                                                                                                  |                                                                                                              |                                                                             |                  |
| Trip current                              | 2 mA to 3 A<br>20 ms to 190 ms                                                                                                                                                                                   | 5.8 % + 240 $\mu$ A                                                                                          |                                                                             | IRE              |
|                                           | 2 mA to 3 A<br>190 ms to 5 s                                                                                                                                                                                     | 1.4 % + 80 $\mu$ A                                                                                           |                                                                             |                  |
| Trip time                                 | 20 ms to 400 ms<br>400 ms to 5 s                                                                                                                                                                                 | 1.0 ms<br>10 ms                                                                                              |                                                                             |                  |
| AC resistance for Loop<br>50 Hz           |                                                                                                                                                                                                                  |                                                                                                              | Laboratory loop 0.20 $\Omega$                                               | IRE              |
| Nominal Ranges                            | 0.2 $\Omega$ to 10 $\Omega$<br>10 $\Omega$ to 100 $\Omega$<br>100 $\Omega$ to 1 k $\Omega$                                                                                                                       | 0.6% + 4.8 m $\Omega$<br>0.6% + 19 m $\Omega$<br>0.6% + 36 m $\Omega$                                        |                                                                             |                  |
| Earth Bond Resistance                     | 0 $\Omega$ to 10 $\Omega$<br>10 $\Omega$ to 100 $\Omega$<br>100 $\Omega$ to 1 k $\Omega$                                                                                                                         | 0.60 % + 4.8 m $\Omega$<br>0.60 % + 19 m $\Omega$<br>0.60 % + 36m $\Omega$                                   |                                                                             | IRE              |
| Earth bond current<br>50 Hz               | 10 mA to 500 mA<br>100 mA to 10 A<br>10 A to 30 A                                                                                                                                                                | 1.8 % + 7.0 mA<br>1.8 % + 70 mA<br>1.8 % + 70 mA                                                             |                                                                             |                  |
| Load                                      | 0.13 kVA                                                                                                                                                                                                         | 6.0 %                                                                                                        |                                                                             |                  |
| Leakage Current<br>At nominal 240 V 50 Hz | 2 mA to 8 mA                                                                                                                                                                                                     | 1.8 % + 11 $\mu$ A                                                                                           |                                                                             | IRE              |
| Insulation Test Voltage                   | 50 V to 1000 V                                                                                                                                                                                                   | 1.2 % + 950 mV                                                                                               |                                                                             |                  |
| Insulation Resistance                     | 10 k $\Omega$ to 100 k $\Omega$<br>101 k $\Omega$ to 1 M $\Omega$<br>1.01 M $\Omega$ to 10 M $\Omega$<br>10.1 M $\Omega$ to 100 M $\Omega$<br>101 M $\Omega$ to 1 G $\Omega$<br>1.01 G $\Omega$ to 10 G $\Omega$ | 0.12 % + 200 m $\Omega$<br>0.12 %<br>1.2 %<br>1.2 %<br>1.4 %<br>7.0 %                                        |                                                                             |                  |
| AC Voltage                                |                                                                                                                                                                                                                  |                                                                                                              |                                                                             |                  |
| Nominal 50 Hz                             | 100 V to 400 V                                                                                                                                                                                                   | 0.25 % + 160 mV                                                                                              |                                                                             | IRE              |



0822  
Accredited to  
ISO/IEC 17025:2017

**Schedule of Accreditation**  
issued by  
**United Kingdom Accreditation Service**  
2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

**Chamois Metrology Limited**  
Issue No: 077 Issue date: 31 October 2019

**Calibration performed by the Organisation at the locations specified**

| Measured Quantity<br>Instrument or Gauge                               | Range                                                                                                                          | Calibration and<br>Measurement<br>Capability (CMC)<br>Expressed as an<br>Expanded<br>Uncertainty ( $k = 2$ ) | Remarks                                       | Location<br>Code |
|------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------|-----------------------------------------------|------------------|
| Continuity Resistance                                                  | 20 mΩ to 1000 Ω                                                                                                                | 0.30 % + 30 mΩ                                                                                               |                                               | IRE              |
| Continuity Current<br>At a nominal 1 Ω                                 | 10 mA to 300 mA                                                                                                                | 1.6 % + 0.80 mA                                                                                              |                                               |                  |
| ELECTRICAL SIMULATION<br>OF TEMPERATURE                                |                                                                                                                                |                                                                                                              |                                               |                  |
| Base Metal Thermocouples                                               | -200 °C to +1400 °C                                                                                                            | 0.10 °C                                                                                                      | Excluding automatic CJC                       |                  |
| Noble Metal Thermocouples                                              | 500 °C to 1800 °C                                                                                                              | 0.11 °C                                                                                                      |                                               |                  |
| Type B (Noble)<br>Type C                                               | 500 °C to 1800 °C<br>0 °C to 2315 °C                                                                                           | 0.28 °C<br>0.10 °C                                                                                           |                                               |                  |
| Base Metal Thermocouples                                               | -200 °C to +1400 °C                                                                                                            | 0.25 °C                                                                                                      | Including automatic CJC                       |                  |
| Noble Metal Thermocouples                                              | 500 °C to 1800 °C                                                                                                              | 0.26 °C                                                                                                      |                                               |                  |
| Type B (Noble)                                                         | 500 °C to 1800 °C                                                                                                              | 0.43 °C                                                                                                      |                                               |                  |
| Cold Junction Compensation                                             | At ambient temperature of 20 °C                                                                                                | 0.15 °C                                                                                                      |                                               |                  |
| Pt 100 resistance<br>thermometer simulation                            | -200 °C to +266 °C                                                                                                             | 0.011 °C                                                                                                     |                                               |                  |
|                                                                        | 266 °C to 830 °C                                                                                                               | 0.015 °C                                                                                                     |                                               |                  |
| Pt 1000 resistance<br>thermometer simulation                           | -200 °C to +266 °C                                                                                                             | 0.070 °C                                                                                                     |                                               |                  |
|                                                                        | 266 °C to 830 °C                                                                                                               | 0.13 °C                                                                                                      |                                               |                  |
| TEMPERATURE                                                            |                                                                                                                                |                                                                                                              |                                               | IRE              |
| Temperature indicators and<br>recorders, with temperature<br>sensor(s) | 0.01 °C (Water Triple Point)<br>-196 °C (LN2)<br>-95 °C to -80 °C<br>-80 °C to +300 °C<br>300 °C to 450 °C<br>450 °C to 650 °C | 0.0030 °C<br>0.015 °C<br>0.025 °C<br>0.015 °C<br>0.027 °C<br>0.094 °C                                        | In a range of liquid and<br>metal media baths |                  |
| Platinum Resistance<br>Thermometers (4 wire)                           | 0.01 °C (Water Triple Point)<br>-196 °C (LN2)<br>-95 °C to -80 °C<br>-80 °C to +300 °C<br>300 °C to 450 °C<br>450 °C to 650 °C | 0.0030 °C<br>0.015 °C<br>0.025 °C<br>0.015 °C<br>0.027 °C<br>0.094 °C                                        | In a range of liquid and<br>metal media baths |                  |
| Metal Block Calibrators and<br>portable liquid baths                   | -100 °C to +100 °C<br>100 °C to 300 °C<br>300 °C to 420 °C<br>420 °C to 650 °C<br>0 °C                                         | 0.030 °C<br>0.038 °C<br>0.15 °C<br>0.16 °C<br>0.020 °C                                                       | Suitable zero reference<br>baths              |                  |



0822  
Accredited to  
ISO/IEC 17025:2017

**Schedule of Accreditation**  
issued by  
**United Kingdom Accreditation Service**  
2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

**Chamois Metrology Limited**  
**Issue No: 077 Issue date: 31 October 2019**

Calibration performed by the Organisation at the locations specified

| Measured Quantity<br>Instrument or Gauge                                             | Range                                                                                                                                                                                            | Calibration and<br>Measurement<br>Capability (CMC)<br>Expressed as an<br>Expanded<br>Uncertainty ( $k = 2$ )                                                                            | Remarks                                      | Location<br>Code |
|--------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------|------------------|
| HUMIDITY<br><br>Dew-point<br><br>Temperature sensors in air<br><br>Relative humidity | -25 °C to +60 °C<br><br>0 °C to 60 °C<br><br>Example conditions<br><br><i>At 0 °C:</i><br>10 %rh to 90 %rh<br><br><i>At 23 °C:</i><br>5 %rh to 95 %rh<br><br><i>At 60 °C:</i><br>5 %rh to 90 %rh | 0.17 °C<br><br>0.10 °C<br><br>Corresponding to<br>above dew-point and<br>temperature<br>uncertainties<br><br>0.20 %rh to 1.1 %rh<br><br>0.20 %rh to 1.1 %rh<br><br>0.20 %rh to 0.80 %rh | Calibrations undertaken in<br>an air chamber | IRE              |
| END                                                                                  |                                                                                                                                                                                                  |                                                                                                                                                                                         |                                              |                  |



0822

Accredited to  
ISO/IEC 17025:2017

**Schedule of Accreditation**  
issued by  
**United Kingdom Accreditation Service**  
2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

**Chamois Metrology Limited**  
Issue No: 077 Issue date: 31 October 2019

Calibration performed by the Organisation at the locations specified

**Appendix - Calibration and Measurement Capabilities**

**Introduction**

The definitive statement of the accreditation status of a calibration laboratory is the Accreditation Certificate and the associated Schedule of Accreditation. This Schedule of Accreditation is a critical document, as it defines the measurement capabilities, ranges and boundaries of the calibration activities for which the organisation holds accreditation.

**Calibration and Measurement Capabilities (CMCs)**

The capabilities provided by accredited calibration laboratories are described by the Calibration and Measurement Capability (CMC), which expresses the lowest uncertainty of measurement that can be achieved during a calibration. If a particular device under calibration itself contributes significantly to the uncertainty (for example, if it has limited resolution or exhibits significant non-repeatability) then the uncertainty quoted on a calibration certificate will be increased to account for such factors. The CIPM-ILAC definition of the CMC is as follows:

A CMC is a calibration and measurement capability available to customers under normal conditions:

- (a) as published in the BIPM key comparison database (KCDB) of the CIPM MRA; or
- (b) as described in the laboratory's scope of accreditation granted by a signatory to the ILAC Arrangement.

The CMC is normally used to describe the uncertainty that appears in an accredited calibration laboratory's schedule of accreditation and is the uncertainty for which the laboratory has been accredited using the procedure that was the subject of assessment. The CMC is calculated according to the procedures given in M3003 and is normally stated as an expanded uncertainty at a coverage probability of 95 %, which usually requires the use of a coverage factor of  $k = 2$ . An accredited laboratory is not permitted to quote an uncertainty that is smaller than the published CMC in certificates issued under its accreditation.

The CMC may be described using various methods in the Schedule of Accreditation:

As a single value that is valid throughout the range.

As an explicit function of the measurand or of a parameter (see below).

As a range of values. The range is stated such that the customer can make a reasonable estimate of the likely uncertainty at any point within the range.

As a matrix or table where the CMCs depend on the values of the measurand and a further quantity.

In graphical form, providing there is sufficient resolution on each axis to obtain at least two significant figures for the CMC.

**Expression of CMCs - symbols and units**

In general, only units of the SI and those units recognised for use with the SI are used to express the values of quantities and of the associated CMCs. Nevertheless, other commonly used units may be used where considered appropriate for the intended audience. For example, the term "ppm" (part per million) is frequently used by manufacturers of test and measurement equipment to specify the performance of their products. Terms like this may be used in Schedules of Accreditation where they are in common use and understood by the users of such equipment, providing their use does not introduce any ambiguity in the capability that is being described.

When the CMC is expressed as an explicit function of the measurand or of a parameter, this often comprises a relative term (e.g., percentage) and an absolute term, i.e. one expressed in the same units as those of the measurand. This form of expression is used to describe the capability that can be achieved over a range of values. Some examples are shown below. It should be noted that these expressions are *not* mathematical formulae but are instead written in a commonly used shorthand for expressing uncertainties - therefore, for purposes of clarity, an indication of how they are to be interpreted is also provided below.

DC voltage, 100 mV to 1 V: 0.0025 % + 5.0  $\mu$ V

Over the range 100 mV to 1 V, the CMC is 0.0025 %·V + 5.0  $\mu$ V, where V is the measured voltage.

Hydraulic pressure, 0.5 MPa to 140 MPa: 0.0036 % + 0.12 ppm/MPa + 4.0 Pa

Over the range 0.5 MPa to 140 MPa, the CMC is 0.0036 %·p + (0.12·10<sup>-6</sup>·p·10<sup>-6</sup>) + 4.0 Pa, where p is the measured pressure in Pa.

It should be noted that the percentage symbol (%) simply represents the number 0.01. In cases where the CMC is stated only as a percentage, this is to be interpreted as meaning percentage of the measured value or indication.

Thus, for example, a CMC of 1.5 % means 1.5 · 0.01 · i, where i is the instrument indication.